



OLEFINS

Sales Specification
Rev. 4 04/2006

Heptene

Properties	Test Methods	Sales Specifications
Appearance	ASTM D4176 / BRCP 4065	Clear, free of suspended matter
Color, Platinum Cobalt	ASTM D1209 / BRCP 4270	40 max
Composition, wt%	DLTM 2.2-1 / BRCP 4425	
C6 & lighter		3 max
C7		93 min
C8 & heavier		4 max
Peroxides, active oxygen, ppm	AMS 300.10 / BRCP 4615	10 max
Specific Gravity, 20/20 °C	ASTM D4052 / BRCP 4843	0.705-0.716
Sulphur, ppm	ASTM D7039 / ASTM D5453 / BRCP 7731	50 max

Heptene inhibited with butylated hydroxytoluene (BHT)

For more information, to request samples and/or to place orders, call: 1 (800) 663-4109

The user may forward, distribute, and/or photocopy this copyrighted document only if it is unaltered and complete. You may not copy this document to a Web site. This information relates only to the material designated and may not be valid for such material used in combination with any other materials or in any process. Typical values are representative of production, may vary over time and may not match the date of publication. All information, to the best of our knowledge and belief, is accurate and reliable as of the date compiled. Moreover, no warranty or guarantee is made as to its accuracy, reliability or completeness nor do we offer any warranty against patent infringement. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. Sampling and testing procedures in effect at the time of production will be used for certification testing. Results may be based on tank certification, manufacturing data, periodic testing, compliance testing, shipment, end of run, rundown tank or most recent restock analysis. We reserve the right to use other test methods in certifying this material.