

Mobil Clean Motor Oil

Premium Automotive Engine Oil

Product Description

Mobil Clean Motor Oil is formulated from quality base stocks combined with the most modern performance additives, including an advanced detergent system to provide excellent engine cleanliness. These oils protect against sludge and engine rust and corrosion under low-temperature operating conditions. Pour depressants and a viscosity index (VI) improver are included, where required, to provide the desired viscosity-temperature and low-temperature fluidity characteristics. Mobil Clean Oil is available in 3 multi-viscosity grades: SAE 5W-20, 5W-30, and 10W-30, Mobil Clean Oil 5W-20 has been introduced to meet the latest requirements of Ford and Honda. It meets the latest Ford Specification WSS-M2C 930-A. Mobil Clean Oil 5W-20, 5W-30 and 10W-30 contain friction-reducing additives. These viscosity grades are classified by the American Petroleum Institute (API) as "Energy Conserving" engine lubricants, and meet ILSAC GF-4.

Features and Benefits

- Excellent engine cleanliness
- Engine protection under a wide variety of operating conditions
- Satisfies the latest oil requirements of gasoline engine manufacturers (5W-20 recommended for certain Ford and Honda's)
- Fuel efficiency (Mobil Oil 5W-20, 5W-30 and 10W-30)
- Excellent protection for high-performance engines
- Helps reduce engine wear and corrosion
- Helps keep engine clean
- Easy cold starting

Applications

Mobil Clean Oil 5W-20 is recommended for vehicles which call for an API certified, 5W-20 viscosity grade engine oil such as 2001 and newer model year Ford automobiles, 1998 and newer model year Honda Accords, and 1996 and newer Honda Civics. It is also recommended for 2005 Chrysler vehicles where a 5W-20 is recommended. This unique viscosity grade should be used only in automobiles that require a 5W-20 lubricant and it is not recommended for use in other vehicles. Mobil Clean Oil 5W-30 and Mobil Clean Oil 10W-30 are recommended for gasoline fueled automobiles and light duty trucks requiring an API SM, SL, SJ or SH product. They meet ILSAC GF-4 (Starburst Certification Symbol). Before using a Mobil Clean Oil, consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and API Service Classification

Due to continual product research and development, the information contained herein is subject to changes without notification. Additional important health and safety information on this product can be found in the Material Safety Data Sheet, which is available online at www.imperialoil.ca/mobil or by contacting Lubricants and Petroleum Specialties, Technical Services, Technical Help Desk: 1-800-268-3183

© 2001 Imperial Oil
© The Mobil logotype and the Pegasus design are registered trademarks of Exxon Mobil Corporation.
™ Trademark of Exxon Mobil Corporation, Imperial Oil, Licensee.



Specifications and Approvals

Mobil Clean Motor Oil meets the following industry specifications:	5W-20	5W-30	10W-30
API SM	X	X	X
API SL	X	X	X
API SJ		X	X
API SH		X	X
ILSAC GF-4	X	X	X

Mobil Clean Motor Oil has the following builder approvals:	5W-20	5W-30	10W-30
Ford WSS-M2C930-A	X		
Ford WSS-M2C929-A		X	
Ford WSS-M2C395-A			X
GM 6094M		X	X
Chrysler MS 6395	X	X	X

Typical Properties

Mobil Clean Motor Oil has the following builder approvals:	5W-20	5W-30	10W-30
Density @ 15°C, Kg/m ³	0.857	0.859	0.869
Pour Point, °C	-30	-33	-30
Flash Point, COC, °C	200	210	215
Viscosity			
cSt at 40°C	47	63	66
cSt at 100°C	8.4	10.7	10.4
CCS, cP	4900@ -30 °C	5500 @ -30 °C	6300@ -25 °C
MRV, cP	15,000@ -35 °C	18,500 @ -35 °C	18,900@ -30 °C
Viscosity Index	157	160	144
Energy Conserving	Yes	Yes	Yes

Due to continual product research and development, the information contained herein is subject to changes without notification. Additional important health and safety information on this product can be found in the Material Safety Data Sheet, which is available online at www.imperialoil.ca/mobil or by contacting Lubricants and Petroleum Specialties, Technical Services, Technical Help Desk: 1-800-268-3183





Mobil

Health and Safety

Mobil Drive Clean is manufactured from high quality petroleum base stocks, carefully blended with selected additives. As with all petroleum products, good personal hygiene and careful handling should always be practiced. Avoid prolonged contact to skin, splashing into the eyes, ingestion or vapour inhalation. Special care is also recommended in handling used motor oils. A Service Data Sheet entitled "Safe Handling of Used Motor Oils" is available on request from you Imperial Oil Representative. Please refer to our Imperial Oil Material Safety Data Sheet for further information.

Note: This product is not controlled under Canadian WHMIS legislation

8-2006

Due to continual product research and development, the information contained herein is subject to changes without notification. Additional important health and safety information on this product can be found in the Material Safety Data Sheet, which is available online at www.imperialoil.ca/mobil or by contacting Lubricants and Petroleum Specialities, Technical Services, Technical Help Desk: 1-800-268-3183

© 2001 Imperial Oil
® The Mobil logotype and the Pegasus design are registered trademarks of Exxon Mobil Corporation.
™ Trademark of Exxon Mobil Corporation, Imperial Oil, Licensee.

