

Mobil 1 MX4T 10W-40 Motorcycle Oil

Our most Advanced Multigrade Synthetic Four-Stroke Motorcycle Engine Oil Technology

Product Description

Mobil 1 MX4T 10W-40 is our most advanced four-stroke motorcycle engine oil for all climate and terrain driving. This product provides the level of performance demanded by today's high performance 4 stroke engine equipped vehicles. The oil is designed to keep these 4-stroke engines running clean protecting even in the extreme operating conditions.

Features & Expected Benefits

Mobil 1 MX4T 10W-40 combines our latest high performance synthetic basestocks technology with our most advanced additives to provide outstanding performance. Regular use of Mobil 1 MX4T 10W-40 maintains power output in 4 stroke engines due to the inherently low traction coefficients of the carefully picked synthetic base stocks. These oils are specially engineered to deliver unsurpassed performance under severe operating conditions in "All Seasons" driving environments. Key features and expected benefits include:

Features	Expected Advantages and Benefits
Optimized frictional properties	Increased power due to reduced frictional losses Excellent engine performance and fuel economy
Exceptional wear protection	Extended engine life
Outstanding thermal and oxidation stability	Fluid film protection at all operating temperatures controlling deposit formation especially at the high operating temperatures found in air-cooled engines
Outstanding low-temperature properties	Effective lubrication at low ambient temperatures enable easy starting, fast wear protection and less drain on electrical system
Excellent detergent/dispersant capability	Outstanding engine cleanliness, smoother and reliable operation
Effective protection from rust and corrosion	Longer life of critical valve train and bearing components

Applications

- Mobil 1 MX4T 10W-40 is specifically recommended for lubrication of various types of four-stroke engines.





Specifications & Approvals

Mobil 1 MX4T 10W-40 meets or exceeds the following industry specifications:

API	SG,SH, SJ/CF
JASO	MA

Typical Properties

Mobil 1 MX4T 10W-40

SAE Grade	10W-40
Viscosity, ASTM D 445	
cSt @ 40°C	86
cSt @ 100°C	13.8
Viscosity Index, ASTM D 2270	164
Sulfated Ash, wt%, ASTM D 874	1.0
Pour Point, °C, ASTM D 97	-54
Flash Point, °C, ASTM D 92	253
Density @ 15°C kg/l, ASTM D 4052	0.873

Precautions

MOBIL 1 MX4T 10W-40 is manufactured from high quality synthetic base oil , carefully blended with selected additives. As with all petroleum products, good personal hygiene and careful handling should always be practiced. Avoid prolonged contact to skin, splashing into the eyes, ingestion or vapour inhalation. Please refer to our Imperial Oil Material Safety Data Sheet for further information.

Note: This product is not controlled under Canadian WHMIS legislation.

The Mobil logotype, the Pegasus design and Mobil 1 with Supersyn are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

